



Key Features

- Direct replacement for Breezaire and Wine Mate
- Dynamic air flow
- 30°F temperature differential
- Flexible mounting bracket
- Advanced digital controller
- Ductable exterior exhaust

Specifications

Model	CX2200	CX3300	CX4400	CX8800
Cellar Size (cu. ft.)	300	650	1000	2000
BTU/h @ 55°F	1453	2049	2962	4754
CFM	118	126	216	374
Dimensions	14.25"W x 13.25"H x 16.38"D	14.25"W x 19.75"H x 21.63"D		16.25"W x 22"H x 22.25"D
Refrigerant	R-134a	R-134a	R-134a	R-134a
HP	1/8	1/6+	1/4+	1/2+
Voltage Rating (20 amp dedicated circuit required)	110V or 220V	110V or 220V	110V or 220V	110V or 220V
Weight (lb.)	65	66	67	74
Amps (Starting/Running)	28 / 4.5	30 / 4.9	32 / 9	36 / 10
dBa (Evaporator/Condenser)	63 / 63	63 / 64	63 / 64	68 / 68
Drainline	3/8" Condensate			
Installation	Through-the-Wall, Partially Ducted			
Thermostat	Advanced electronic control system			
Temp. Delta	30°F temperature differential (maintains proper cellar temperature when exhaust environment does not exceed 85°F)			
Warranty	2-year parts and labor / 5-year compressor			

Optional Accessories

Exhaust ducting kit, exterior housing, rear power cord

