



Key Features

- Redesigned for improved performance and easier maintenance
- Ultra-quiet and efficient operation
- Advanced electronic control system
- Liquid bottle probe
- Humidity control 60 - 70%
- Energy saving mode
- Alarm capabilities
- Improved, flexible installation
- 55°F temperature differential



Features

WhisperKOOL has a solution to the most stubborn of small cellar cooling roadblocks. This compact system cools up to 500 cubic feet with the compressor located in a remote location and the evaporator (cold side) mounted in the cellar. Since space in a small cellar is vital, the Platinum Mini-Split offers a compact size paired with powerful efficiency. The unit is equipped with our Platinum Series controller utilizing Advanced System Protection Technology. This features a series of strategically placed monitoring probes, which insure efficient performance and long cooling unit life. The controller is easy to operate and has features such as adjustable humidity control, energy saving modes, quick chill mode and anti-frost function. The Platinum Mini-Split gives anyone the opportunity to have a top-quality wine cellar.

Our Platinum Mini Split system has been redesigned for easier care and maintenance. We've moved the evaporator coil to a new location and create a unit that can be maintained without removing it from the wall. This improved design will make servicing the system easier and maintain peak operating conditions.

Specifications

| | |
|-------------------------|--|
| Cellar Size | 500 cu. ft. |
| BTUh @ 55° | 1620 1540 |
| CFM | 99 |
| Dimensions | Evaporator: 20"W x 10.50"H x 13"D Condenser: 11.5"W x 9.9"H x 16"D |
| Refrigerant | R-134a |
| HP | 1/5 |
| Voltage Reading | 115V or 230V - 20 amp dedicated circuit required |
| Weight | Evaporator: 25lbs / Condenser: 41lbs |
| AMPS (starting/running) | Evaporator: 2/1 Condenser: 11/3.8 |
| dBA | Evaporator: 51 / Condenser: 65 |
| Insulated Line Set | 3/8" Suction 1/4" Liquid |
| Drainline | 1/2" Condensate |
| Installation | Evaporator is installed in the cellar, Condenser is installed up to 100 line ft. away and with the installation specifications found in the owners manual. Allow for adequate airflow. |
| Thermostat | Digital Control Display |
| Temp. Delta | 55°F temperature differential (maintains proper cellar temperature when exhaust environment does not exceed 110°F) |
| Warranty | 2 year parts and labor |

Optional Accessories

Exterior Condenser Housing, Built-In Humidity Option