



**CC 2600 SYSTEM  
CONSISTS OF:**

Air Cooled condensing unit with system parameters for 2600 btu when:  
@ 38°F suction & 90°F ambient temperature with a 10° temperature differential of air  
flow over fan coil



<b>Condensing Unit:</b>	CU 26
<b>Horsepower:</b>	1/4
<b>Refrigerant:</b>	R134a
<b>Voltage:</b>	115/1/60
<b>MCA (Amps):</b>	5.3
<b>Length (In.):</b>	17.0
<b>Width (In.):</b>	12.0
<b>Height (In.):</b>	9.4
<b>Connection Suction (In.):</b>	3/8s
<b>Connection Liquid (In.):</b>	1/4 f
<b>Compressor:</b>	NEK6170Z
<b>Oil:</b>	Polyol Ester
<b>Receiver Cap. 90 % Full (Lbs.):</b>	2.4
<b>Shipping Weight (Lbs.):</b>	41



<b>Evaporator:</b>	
<b>Part No.:</b>	CC2FC
<b>Voltage:</b>	115v
<b>MCA (Amps):</b>	0.4a
<b>Length (In.):</b>	18"
<b>Width (In.):</b>	9.5"
<b>Height (In.):</b>	9.5"
<b>Shipping Weight (Lbs.):</b>	20 lbs.
<b>Connection Suction (In.):</b>	3/8"
<b>Connection Liquid (In.):</b>	1/4"
<b>Drain Line (In.):</b>	1/2"
<b>CFM:</b>	300

**System Line Set:**

<b>Suction:</b>	3/8"
<b>Liquid:</b>	1/4"