



CC 6600 TE SYSTEM  
CONSISTS OF:

Air cooled condensing unit with system parameters for 6600 btu when:  
@ 38°F suction & 90°F ambient temperature with a 10° temperature differential of air flow  
over fan coil



**Condensing Unit:**

<b>Horsepower:</b>	1/2
<b>Refrigerant:</b>	R134a
<b>Voltage:</b>	115/1/60
<b>MCA (Amps):</b>	15.5
<b>Length (In.):</b>	20.6
<b>Width (In.):</b>	13.9
<b>Height (In.):</b>	13.2
<b>Connection Suction (In.):</b>	1/2 S
<b>Connection Liquid (In.):</b>	¼ S
<b>Connection Type:</b>	Flare
<b>Compressor:</b>	AKA4476YXA
<b>Oil:</b>	Polyol Ester
<b>Receiver Cap. 90 % Full (Lbs.):</b>	3.5
<b>Shipping Weight (Lbs.):</b>	83



**Evaporator:**

<b>Part No.:</b>	2/CC 3
<b>Voltage:</b>	115v
<b>MCA (Amps):</b>	1.5a
<b>Length (In.):</b>	20"
<b>Width (In.):</b>	9.5"
<b>Height (In.):</b>	9.5"
<b>Shipping Weight (Lbs.):</b>	24 lbs.
<b>Connection Suction (In.):</b>	3/8"
<b>Connection Liquid (In.):</b>	1/4"
<b>Drain Line (In.):</b>	1/2"
<b>CFM:</b>	400

**System Line Set:**

<b>Suction:</b>	1/2"
<b>Liquid:</b>	1/4"