



Key Features

- Customizable front panel
- 2-speed fan airflow control
- E-coated coils for durability
- Front-facing digital controller
- 30°F temperature differential
- Above-door mounting capability
- Bottle probe temperature control
- Self-contained through-wall design
- Evaporates up to 3 oz/hr condensate
- UV-C Lighting System optional add-on

Features

Designed for compact efficiency, the Slimline LS mounts above the cellar door to utilize unused space and delivers 20% more cooling capacity than the previous Slimline 2500/3300 in a modern, low-profile design. Featuring centrifugal blowers for quiet operation, an intelligent ECM fan for optimized airflow, and an enhanced condensate management system, the Slimline LS provides exceptional performance with minimal noise. The system also offers an optional UV-C Lighting System for mold prevention and an interchangeable decorative grille to complement luxury cellar aesthetics.

Specifications

Fan Speed	Low	Medium
Cellar Size	300 cu. ft.*	650 cu. ft.*
BTU/h (60°F condenser air intake temperature)	2601/1961 (total/sensible)	3032/2413 (total/sensible)
BTU/h (75°F condenser air intake temperature)	2635/1951 (total/sensible)	2904/2309 (total/sensible)
BTU/h (85°F condenser air intake temperature)	2396/1870 (total/sensible)	2612/2158 (total/sensible)
BTU/h (95°F condenser air intake temperature)	2205/1704 (total/sensible)	2392/2008 (total/sensible)
CFM	81	111
Dimensions	21.75"L x 22.16"W x 10.33"H	
Refrigerant	R-134a/R-513a	
HP	1/5	
Voltage Rating	115V (15 amp dedicated circuit required); 230V (subject to availability)	
Weight (lbs)	81 lbs. without packaging, 90 lbs. with packaging	
Amps	4.3 (running amps)	
Drain Line	1/2" ID clear plastic tubing (not provided)	
Installation	Through the wall, ideally above a doorway	
Thermostat	Advanced digital display, liquid-temperature-measuring bottle probe (retractable cable)	
Temp. Delta	Can maintain a 55°F cellar temperature with up to 85°F condenser air intake temperature	
Warranty	2-year limited warranty & up to an additional (6) month grace period for install / 5-year limited warranty (compressor)	

*Suggested cubic footage rating assumes cellar is properly sealed and insulated with a minimum R19 insulation value. Materials such as glass, stone, concrete, etc., will negatively affect the insulation value. Each wine cellar is unique, and heat load calculations should always be performed prior to selecting a cooling unit. WhisperKOOL reserves the right to make changes to this document without prior notice at its sole discretion.

