

Tomorrow's Weather Today

302-604

Indoor Comfort Level Station

Quick setup manual

Introduction

The Indoor Comfort Level Station is an ideal measuring instrument for checking room ambient conditions.

Checking indoor temperature and humidity can help achieve a comfortable and healthy living environment and may even save you heating costs.

Features:

- Digital time
- Indoor temperature (°F or °C)
- Indoor relative humidity (%RH)
- Minimum and Maximum temperature and humidity records.
- Comfort level icon (smiley face) for humidity levels between 40% - 60%RH.
- Display large temperature or large humidity with the touch of a button.
- Wall hanging or free standing.
- Temperature range: -4° F to 122° F (-20° C to 50° C).
- "Lo" icon when temperature is below -4°F (-20°).
- Humidity range 20% to 99% RH.
- CR 2032 button cell battery included.

Set up:


- Remove the stand (E) from the back of the station by carefully pulling it downwards.
- Open the battery compartment (F) by turning the lid with a coin counter clockwise.
- Remove the insulation strip from the battery.
- Close the battery compartment again.
- All LCD segments will light up for about a few seconds.
- The unit is now ready to use.
- The upper display shows the time and the comfort level, the middle display shows the current temperature and the lower display the relative humidity

Buttons:

A: SET button
B: SWITCH button
C: MAX/MIN button

Housing:

D: Wall mounting hole E: Removable stand F: Battery compartment



Display with removable stand.

Set Time:

Press and hold SET button for 3 seconds, to enter the time set mode.

- HOUR: The Hour digit is flashing. Press and release the SWITCH button to adjust the Hours. Be sure to AM or PM is showing as appropriate.
- MINUTES: Press and release the SET button again the Minutes digit is flashing. Press and release the SWITCH button to adjust the minutes. Hold the SWITCH button to change the Minutes quickly.
- **CONFIRM**: Press and release the SET button to confirm the time and return to a normal display.

Fahrenheit or Celsius:

 Press and release the SET button to change between °C (Celsius) or °F (Fahrenheit) as temperature unit in normal mode.

NOTE: With Fahrenheit as temperature unit, the clock automatically switches to the 12 HR system (PM appears on the display after noon).

Comfort Level Icon: ©

 When the humidity is between 40% and 60% a smiling face icon will display in the upper right corner of the station to indicate the comfort level of indoor climate.

MAX/MIN Values:

VIEW: Press and release the MAX/MIN button. MAX appears on the display. The maximum temperature and humidity are displayed. Press and release the MAX/MIN button again. MIN appears on the display. The minimum temperature and humidity are displayed. Press MAX/MIN button again to return to normal mode.

 RESET: Press and release the MAX/MIN button to show MAX or MIN. Hold the SET button in the respective mode to clear the recorded MAX/MIN reading. The temperature and humidity will appear as: --.- °F and --.-% on the display.

Display options:

 Press and release the SWITCH button, to choose between the large-scale display of temperature or humidity.

Positioning and mounting:

With the removable stand the instrument can be placed onto any flat surface or wall mounted at the desired location by the wall mounting hole at the back of the unit.

Battery replacement:

Change the battery CR 2032 button cell when the battery symbol appears on the display

- Remove the stand (E) from the back of the station by carefully pulling it downwards.
- Open the battery compartment (F) by turning the lid with a coin counter clockwise.
- Remove the old battery and install a fresh CR 2032 battery. Observe correct polarity (+ facing up).
- Close the battery compartment again.

Low batteries should be changed soon to avoid the damage resulting from a leaking battery.

Attention:

If you notice that the LCD appears faint or is not working properly, try a fresh battery before contacting customer support. We recommend that you replace the batteries in all units regularly to ensure optimum accuracy of this unit.

Help us to keep our environment clean. Please do not dispose of old electronic devices and empty batteries in household waste. To protect the environment, take them to your retail store or to appropriate collection sites according to national or local regulations.

Maintenance:

- Keep the instrument in a dry place.
- Do not expose the instrument to extreme temperatures, vibration or shock.
- Clean it with a soft damp cloth. Do not use solvents or scouring agents.
- If the unit does not work properly, change the battery.

Intended usage, safety information:

- The product is not a toy. Keep it out of reach of children.
- The product is not to be used for medical purpose or for public information, but is determined for home use only.
- The specifications of this product may change without prior notice.
- Improper use or unauthorized opening of housing will void the warranty.

Specifications

Temperature range: -4°F....122°F (-20°C...50°C)
Precision: 32°F...+104°F ± 2°F, otherwise 3°F
Resolution: 0.1°F

Measuring range humidity: 20%...99%

Accuracy: 35%...75% ±4%

"Lo": = temperature is lower than -4°F

Battery: CR 2032 button cell battery

Product size: 4.125" L x 1.625" W x 4.125" H

WARRANTY INFORMATION

La Crosse Technology, Ltd provides a 1-year limited warranty on this product against manufacturing defects in materials and workmanship.

This limited warranty begins on the original date of purchase, is valid only on products purchased and used in North America and only to the original purchaser of this product. To receive warranty service, the purchaser must contact La Crosse Technology, Ltd for problem determination and service procedures. Warranty service can only be performed by a La Crosse Technology, Ltd authorized service center. The original dated bill of sale must be presented upon request as proof of purchase to La Crosse Technology, Ltd or La Crosse Technology, Ltd's authorized service center.

La Crosse Technology, Ltd will repair or replace this product, at our option and at no charge as stipulated herein, with new or reconditioned parts or products if found to be defective during the limited warranty period specified above. All replaced parts and products become the property of La Crosse Technology, Ltd and must be returned to La Crosse Technology, Ltd.

Replacement parts and products assume the remaining original warranty, or ninety (90) days, whichever is longer. La Crosse Technology, Ltd will pay all expenses for labor and materials for all repairs covered by this warranty. If necessary repairs are not covered by this warranty, or if a product is examined which is not in need or repair, you will be charged for the repairs or examination.

The owner must pay any shipping charges incurred in getting your La Crosse Technology, Ltd product to a La Crosse Technology, Ltd authorized service center.

Your La Crosse Technology, Ltd warranty covers all defects in material and workmanship with the following specified exceptions: (1) damage caused by accident, unreasonable use or neglect (including the lack of reasonable and necessary maintenance); (2) damage occurring during shipment (claims must be presented to the carrier); (3) damage to, or deterioration of, any accessory or decorative surface; (4) damage resulting from failure to follow instructions contained in your owner's manual; (5) damage resulting from the performance of repairs or alterations by someone other than an authorized La Crosse Technology, Ltd authorized service center; (6) units used for other than home use (7) applications and uses that this product was not intended or (8) the products inability to receive a signal due to any source of interference.

This warranty covers only actual defects within the product itself, and does not cover the cost of installation or removal from a fixed installation, normal set-up or adjustments, claims based on misrepresentation by the seller or performance variations resulting from installation-related circumstances.

LA CROSSE TECHNOLOGY, LTD WILL NOT ASSUME LIABILITY FOR INCIDENTAL, CONSEQUENTIAL, PUNITIVE, OR OTHER SIMILAR DAMAGES ASSOCIATED WITH THE OPERATION OR MALFUNCTION OF THIS PRODUCT. THIS PRODUCT IS NOT TO BE USED FOR MEDICAL PURPOSES OR FOR PUBLIC INFORMATION. THIS PRODUCT IS NOT A TOY. KEEP OUT OF CHILDREN'S REACH.

This warranty gives you specific legal rights. You may also have other rights specific to your State. Some States do no allow the exclusion of consequential or incidental damages therefore the above exclusion of limitation may not apply to you.

For warranty work, technical support, or information contact:

La Crosse Technology 2817 Losey Blvd. S. La Crosse, WI 54601 The instruction manual is available at: www.lacrossetechnology.com/support

Le manuel d'instruction est disponible sur: www.lacrossetechnology.com/support

El manual de instrucciones está disponible en: www.lacrossetechnology.com/support

All rights reserved. This handbook must not be reproduced in any form, even in excerpts, or duplicated or processed using electronic, mechanical or chemical procedures without written permission of the publisher.

This handbook may contain mistakes and printing errors. The information in this handbook is regularly checked and corrections made in the next issue. We accept no liability for technical mistakes or printing errors, or their consequences.

All trademarks and patents are acknowledged.

Printed in China